

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. A method of transmitting information along a fence conductor characterised in that the information is embedded within and spread across a series of short high voltage signal bursts of a high frequency .
2. The method according to claim 1 wherein the frequency range is between substantially 50 to 190 kHz.
3. The method according to claim 2 wherein the signal bursts have an amplitude in the range of a fraction of one volt up to a maximum of several thousand volts.
4. The method according to claim 3 wherein the duration of individual bursts is in the range of 100 microseconds to 1000 microseconds.
5. <sup>Sub A1</sup> The method according to claim 1 or 4 wherein each signal burst is encoded with one or more digital bits.
6. The method according to claim 1 or 4 wherein each signal burst contains one or more digital bits are

27  
encoded on the high frequency signal bursts using frequency modulation.

7. A remote control apparatus for an electric fence the apparatus including a housing, contact means for contacting a conductor on the electric fence and generating means for generating information embedded within a series of short signal bursts of a frequency within a predetermined frequency range.
8. Apparatus as claimed in claim 7 wherein the housing includes a volt/current meter.
9. Apparatus as claimed in claim 8 further including separate contact means to provide for voltage measurement by the volt/current meter.
10. Apparatus as claimed in claim 7 wherein the frequency is in the range of 50 to 190 kHz.
11. Apparatus as claimed in claim 10 further including high voltage isolation means at the apparatus output, said high voltage isolation means including a capacitor of small value and rated to withstand voltages <sup>normally</sup> normal present on an electric fence installation.

add  
A2